



SERIES FEATURES

 Motors powered by 230V

PRODUCT FEATURES

 Self-learning

 Opening and closing deceleration system

Characteristics PRG 230V

Electronic programmers microprocessor controlled for 230V motors

Mains power supply 230Vac
Motor output 230Vac
Protection grade IP55
Fireproofing grade V2
Interface for a standard slot-in radio card
Command inputs: TA, TC, TD, TB

Electronic devices for the control of automatic opening systems. Specially studied and designed for this type of use, these Cardin programmers are fitted with digital "step by step" time programming which is easily carried out in real time while the gate is moving thus reducing the installation time. The simplified programming method uses one or two buttons (depending on the version) allowing all functions to be programmed rapidly.

In the double gate/door version the programming procedure is guided by a LED display. The complete range of products have been designed and constructed in accordance with the safety standards in force and feature automatic, semi-automatic, manual and remote control functions (the product takes a Cardin standard slot-in receiver card).

Electronic devices for the control of automatic opening systems with one or two gate leaves: sliding gates, hinged gates and garage doors powered by 230Vac. The complete range of programmers simplifies and solves all possible installation problems. The high product-quality level together with accurate design and a selective choice of materials allows trouble free operation and maximum reliability under all kinds of working conditions.

Product features PRG230M2

Electronic programmers for the management of two 230V-motors

The appliance is fitted with an interface for the insertion of a standard Cardin radio receiver card. Digital work time control separately memorised for each gate leaf guided by a 6-digit display. Possible operation without mechanical travel limits. Torque setting.

Maximum power initial thrust control, torque limitation and deceleration management with deceleration zone control.

Suitable for the control of automatic gates and doors with two 230V motors.



> ULTIMATE CARDIN App


PRG230M2 - ELECTRONIC PROGRAMMERS

Electronic programmers for the management of two 230V-motors

GENERAL CHARACTERISTICS

Single phase mains power supply 50/60Hz	Vac	230
Power input	W	1000
Nominal electrical input	A	4.6
Power output for 2 motors	W	470 + 470
Operating temperature range	°C	-20...+55
Protection grade	IP	55
Insulation class	Cls	II

OVERALL DIMENSIONS



> ULTIMATE CARDIN App