



PRODUCT FEATURES



Built-in radio receiver card



433MHz



S449

Characteristics PRG 230V

Electronic programmers microprocessor controlled for 230V motors

Mains power supply 230Vac

Motor output 230Vac

Protection grade IP55

Fireproofing grade V2

Interface for a standard slot-in radio card

Command inputs: TA, TC, TD, TB

Electronic devices for the control of automatic opening systems. Specially studied and designed for this type of use, these Cardin programmers are fitted with digital "step by step" time programming which is easily carried out in real time while the gate is moving thus reducing the installation time. The simplified programming method uses one or two buttons (depending on the version) allowing all functions to be programmed rapidly.

In the double gate/door version the programming procedure is guided by a LED display. The complete range of products have been designed and constructed in accordance with the safety standards in force and feature automatic, semi-automatic, manual and remote control functions (the product takes a Cardin standard slot-in receiver card).

Electronic devices for the control of automatic opening systems with one or two gate leaves: sliding gates, hinged gates and garage doors powered by 230Vac. The complete range of programmers simplifies and solves all possible installation problems. The high product-quality level together with accurate design and a selective choice of materials allows trouble free operation and maximum reliability under all kinds of working conditions.

Product features PRG304ETC

ECU with external control buttons

Electronic programmer for the control of one 230V motor with maximum power yield 650W

Digital work time control. Command inputs: TA, TC and TB. Security inputs: photocells, safety edge (N.C. contact or 8.2 kΩ), digital safety edge. Output for a courtesy light 230Vac 300W and for a LED warning light.

The appliance is supplied with a S449, 433MHz, FM decoder.

External control buttons on the front panel.

Suitable for the control of automatic rolling shutters.




> ULTIMATE CARDIN App

GENERAL CHARACTERISTICS

Single phase mains power supply 50/60Hz	Vac	230
Power input	W	950
Nominal electrical input	A	4.4
Power output for 1 motor	W	600
Operating temperature range	°C	-20...+55
Protection grade	IP	55
Insulation class	Cls	II

OVERALL DIMENSIONS



> ULTIMATE CARDIN App