



SERIES FEATURES

 Motors powered by 230V

PRODUCT FEATURES

 Self-learning

 Multi-decoding open collector

Characteristics PRG TS 230V

Electronic programmers for 230V rolling grills and rolling shutters

Mains power supply 230Vac

Motor output 230Vac

Motor power 1300W

Protection grade IP55

Fireproofing grade V2

Electronic devices for the control of 230V automatic rolling grills and rolling shutters. Specially studied and designed for this type of use, these Cardin programmers are fitted with digital time programming.

Dedicated to 230Vac they intelligently manage the movement of the gate.

The functions are programmed via dip-switches.

The electronic programmers T21X and T21B have been designed and constructed in accordance with the safety standards in force and feature automatic, semi-automatic, remote control and deadman operating functions and a 230V non-flashing warning light.

They are also factory set for the insertion of an open collector receiver card that guarantees compatibility with all the radio control series available in the Cardin catalogue.

The high product-quality level together with accurate design and a selective choice of materials allows trouble free operation and maximum reliability under all kinds of working conditions.

The command card T1 is ideal for connecting the digital selector switch APRO and supplies a power output of 1000W for the dead man control of rolling grills or rolling shutters.

Product features T21X

Electronic programmer controlling one 230V motor

ECU for rolling grills or rolling shutters max. 1300W. Ideal for tubular motors or rolling shutters and fitted with torque limitation, a programmable 24V warning light output (flashing or continuous activation) and a 230V courtesy light output.

Protection grade IP55

Overall dimensions 135 x 175 x 85



> ULTIMATE CARDIN App

GENERAL CHARACTERISTICS


Single phase mains power supply 50/60Hz	Vac	230
Power input	W	1500
Nominal electrical input	A	6.3
Power output for 1 motor	W	1300
Operating temperature range	°C	-20...+55
Protection grade	IP	55
Insulation class	Cls	II

CONNECTIVITY

Optional slot-in receiver card

OC2

OVERALL DIMENSIONS



> ULTIMATE CARDIN App