



Characteristics Multi-beam photoelectric cells

CDR-REDS

Power supply 10-30Vdc

Protection grade IP67

Blanking function

Maximum range 12m

A safety system consisting of two profiles located at the sides of the passage to detect, at various heights, any obstacles or persons and to prevent their impact with the moving part.

Such systems are particularly suited to sectional doors and fast curtains, as the units can be installed on opposite sides of the opening (inside/outside) or concealed within the tracks.

The infra-red barrier adapts to various installations through an internal calibration of the range and the continuous synchronisation of each channel (beam). The angle of the infrared beam and the opening angle of the optics ($\pm 10^\circ$) facilitates and allows installation even when the profiles are not perfectly aligned.

The BLANKING function allows the units to be installed within the guide tracks of an industrial door, where door movement occurs within the protected area, interrupting beams sequentially from top to bottom. This specific function ensures that the system can distinguish between the door closing and another object, ignoring beams that are blocked by door movement and leaving only the remaining beams active at the bottom to detect an object below the door edge.

They have a range of up to 12m and a 14mm profile, 40% thinner than previous models. They have an M8 connector and the ability to be synchronised in cases where more than one pair of multi-beam photocells are installed.

Product features CDR-RED2.0

Multi-beam infrared barrier

A safety system consisting of two profiles located at the sides of the passage to detect, at various heights, any obstacles or persons and to prevent their impact with the moving part.

Technical description

Power supply 12-30Vdc/24Vac

Controlled range for gates from 1 to 10m

Height 1950 mm x 16 beams

Anodised and sealed aluminium profile IP67

Units supplied with cable (Tx 15m / Rx 5m)

Low profile (15 mm)



> ULTIMATE CARDIN App

CDR-RED2.0 - INFRARED MODULATED BARRIERS

Multi-beam infrared barrier



GENERAL CHARACTERISTICS

Power supply	Vac/dc	24
Operating temperature range	°C	-20...+55
Protection grade	IP	67



> ULTIMATE CARDIN App

CARDIN ELETTRONICA S.p.a. - Via del lavoro, 73 - Z.I. Cimavilla - 31013 Codognè (TV) - Italy
tel. +39 0438 404011 - tel. hotline italia +39 0438 404150 - fax. 0438 401831 - e-mail italy sales.office.it@cardin.it - e-mail europe sales.office@cardin.it - www.cardin.it