



SERIES FEATURES

-  Multi-decoding open collector
-  Magnetic encoder control
-  Self-learning

PRODUCT FEATURES

-  Motors powered by 230V
-  Opening and closing deceleration system
-  Bluetooth compatible
-  Master - Slave setting

Characteristics PRG T 230V / 400V

Electronic programmers single phase - three phase motors for industrial installations

Mains power supply 230Vac / 400Vac

Single phase motor output 230Vac

Three phase motor output 400V3~

Protection grade IP55

Fireproofing grade V2

Electronic devices for the control of automatic opening systems with one or two gate leaves. Specially studied and designed for this type of use, these Cardin programmers are fitted with digital time programming.

Dedicated to 230Vac and 400V3~ motors (T400) they intelligently manage the movement of the gate.

The appliances either work with encoder controlled or timer controlled gate positioning (automatic system detection).

The complete range of products have been designed and constructed in accordance with the safety standards in force and feature automatic, semi-automatic and remote control functions.

Compatible with the INTPRG-4G/INTPRGN-WF system (Except T400) that allows you to control and program the system parameters from a remote location.

The complete range of programmers simplifies and solves all possible installation problems. The high product-quality level together with accurate design and a selective choice of materials allows trouble free operation and maximum reliability under all kinds of working conditions.

Open collector

The product range is factory set for the insertion of an open collector receiver card that guarantees compatibility with all the radio control series available in the Cardin catalogue.

Product features T101E

Electronic programmer for one 230V motor

Encoder controlled programmer with torque limitation, deceleration and safety device exclusion via dip-switch.

Double 8,2kΩ inputs for connecting safety edges.

It is possible to connect two control units in Master/Slave configuration for installations with paired gates.



> ULTIMATE CARDIN App

T101E - ELECTRONIC PROGRAMMERS

Electronic programmer for one 230V motor



GENERAL CHARACTERISTICS


Single phase mains power supply 50/60Hz	Vac	230
Power input	W	1500
Nominal electrical input	A	6.3
Power output for 1 motor	W	1100
Operating temperature range	°C	-20...+55
Protection grade	IP	55
Insulation class	Cls	II

CONNECTIVITY

Optional slot-in receiver card

OC2

OVERALL DIMENSIONS



> ULTIMATE CARDIN App

CARDIN ELETTRONICA S.p.a. - Via del lavoro, 73 - Z.I. Cimavilla - 31013 Codognè (TV) - Italy
tel. +39 0438 404011 - tel. hotline italia +39 0438 404150 - fax. 0438 401831 - e-mail italy.sales.office@cardin.it - e-mail europe.sales.office@cardin.it - www.cardin.it