



Characteristics WARNING LIGHTS

Electronic warning lights with LED technology

Power supply 24Vac-dc / 230Vac

Led illumination

Fixed position and adjustable versions

The ample range of electronic warning lights are valid visual warning systems for the movement of automatic devices, built according to the safety standards in force and using LED technology. Highly efficient and adaptable to all situations they satisfy the needs of a modern installation.

The warning lights are available in 24V and 230V versions as follows:

ICON / ICON-WH - 24Vac-dc - 230Vac on-board selectable power supply, multi-led.

ICONX - 24Vac-dc on-board selectable power supply, multi-led RGB.

MOLLIGHT4 - 24Vac-dc eight leds.

MOLLIGHT4X - 230Vac eight leds.

LACOLED - 24Vac-dc - 230Vac on-board selectable power supply, multi-led.

LPXLAMP - 24Vac-dc - 230Vac on-board selectable power supply, multi-led.

WALL - 24Vdc strip of led lighting.

WALL + AL2VA - 230Vac output 24Vdc strip of led lighting.

The shape and thicknesses used for the protective parts and the attention to detail paid to the sealing gaskets for all the critical joints make the entire structure weather-proof and immune to vandalism.

All in all this is a unique and unmistakeable appliance, an effective warning system both before and during the activation of the automatic opening device whilst at the same time underlining the quality and service given by a Cardin System.

Product features LPXLAMP-OR

24-230V LED warning light, orange

Suitable for fitting to all types of system, its compact size and simplicity of installation makes it ideal for residential systems. The lamp cover can be adjusted in height, thus allowing horizontal installations with a minimum outcrop.

On-board selectable power supply: 24Vac-dc - 230Vac.

Duty cycle 70%.

Fixed light - flashing light selection jumper.

Adjustable light cover.

Protection grade IP55



> ULTIMATE CARDIN App

LPXLAMP-OR - WARNING LIGHTS


24-230V LED warning light, orange



GENERAL CHARACTERISTICS

Power supply	Vac/dc	24 / 230
Operating temperature range	°C	-20...+55
Protection grade	IP	55

OVERALL DIMENSIONS



> ULTIMATE CARDIN App

CARDIN ELETTRONICA S.p.a. - Via del lavoro, 73 - Z.I. Cimavilla - 31013 Codognè (TV) - Italy
tel. +39 0438 404011 - tel. hotline italia +39 0438 404150 - fax. 0438 401831 - e-mail italy sales.office.it@cardin.it - e-mail europe sales.office@cardin.it - www.cardin.it