



### SERIES FEATURES

 Motors powered by 230V

### Characteristics PRG 230V

Electronic programmers microprocessor controlled for 230V motors

Mains power supply 230Vac  
Motor output 230Vac  
Protection grade IP55  
Fireproofing grade V2  
Interface for a standard slot-in radio card  
Command inputs: TA, TC, TD, TB

Electronic devices for the control of automatic opening systems. Specially studied and designed for this type of use, these Cardin programmers are fitted with digital "step by step" time programming which is easily carried out in real time while the gate is moving thus reducing the installation time. The simplified programming method uses one or two buttons (depending on the version) allowing all functions to be programmed rapidly.

In the double gate/door version the programming procedure is guided by a LED display. The complete range of products have been designed and constructed in accordance with the safety standards in force and feature automatic, semi-automatic, manual and remote control functions (the product takes a Cardin standard slot-in receiver card).

Electronic devices for the control of automatic opening systems with one or two gate leaves: sliding gates, hinged gates and garage doors powered by 230Vac. The complete range of programmers simplifies and solves all possible installation problems. The high product-quality level together with accurate design and a selective choice of materials allows trouble free operation and maximum reliability under all kinds of working conditions.

### Product features PRG302E

Electronic programmer for the control of one 230V motor with maximum power yield 600W

Digital work time control. Possible operation without mechanical travel limits. Command inputs: TA, TC, TD, TB.

The appliance is fitted with an interface for the insertion of a standard Cardin radio receiver card.

Suitable for the control of automatic road barriers.

The programmer comes complete with cable glands  $\varnothing 2 \times \varnothing 9\text{mm} + \varnothing 2 \times \varnothing 16\text{mm}$ .



> ULTIMATE CARDIN App

## PRG302E - ELECTRONIC PROGRAMMERS

Electronic programmer for the control of one 230V motor with maximum power yield 600W




### GENERAL CHARACTERISTICS

Single phase mains power supply 50/60Hz	Vac	230
Power input	W	600
Nominal electrical input	A	2.6
Power output for 1 motor	W	450
Operating temperature range	°C	-20...+55
Protection grade	IP	55
Insulation class	Cls	II

### CONNECTIVITY

Optional slot-in receiver card RQS

### OVERALL DIMENSIONS



> ULTIMATE CARDIN App